

① 3U rackmount kit ② 2.5" SSD or 3.5" HDD hotswap mobile rack ③ SFX (MicroATX) power supply with PFC ④ USB/LED/Switch

Front or Rear side of chassis accessible



One of the features of the 3U C335B is that the depth is only 335mm, the I/O and SFX (MicroATX) power supply and the optional hot-swappable SSD/HDD mobile rack can be installed at front or rear side of chassis, even pedestal as a tower chassis is compatible. Less than 280mm depth of Nvidia or other brands of GPU cards are compatible with this 3U chassis very well. With its features which can meet the needs of AI high-end computing nowadays.

Specification

- * Storage space: One 5.25" ODD bay
- * I/O front or rear or pedestal type can be achieved without additional fixing brackets
- * Intake fan (option): 60mmx25mm 3 fans installed at filter side under the 5.25" ODD
- * Exhaust fan (option): 60mmx25mm 1 fan with fan guard above the top of I/O section
- * Major sheet metal by 1.2mm~2.0mm thickness SGCC ultra-high strength patternless
- * Standard equipped with two USB 3.0 and LAN/HDD/Power LED indicator light display
- * Compatible PSU: SFX (MicroATX) PSU with PFC (D.100 x W.125 x H.63.5 /mm)
- * Compatible MB: CEB1.01 (12"x10.5"), ATX(12"x9.6"), mATX(9.6"x9.6"), ITX(6.7"x6.7")
- * 8-slot rear panel supports 7-slot NVIDIA or other GPU cards (max. 280mm)
- * Standard paint: scratch-resistant Black textured paint on surface of chassis
- * Genesys Group chassis with build-in electronics in global 3 years warranty
- * Chassis dimension: 19" x 3U x 335mm (13.19" deep)
- * Accessory: various screw x54, #6 MB copper stand-off x3, rackmount kit x1, foot x4
- * Package: NW 5.23 KGM, GW 6.71 KGM, 1.92 CUFT (carton size at 55x45x22cm)

Ordering Information

Model#: C335B, 3U GPU I/O front-rear access chassis

Option A: FSP850-57SBB, SFX 850W power supply with PFC (D.100 x W.125 x H.63.5 /mm)

Option B-1: SUNTAI6025, Suntai 60mm x 25mm two-ball bearing fan (intake, can install 3 fans under the 5.25" ODD)

Option B-2: SUNTAI6025-6CM-IRONNRT, Suntai 60mm x 25mm two-ball bearing fan & fan guard (exhaust, can install 1 fan above I/O)

Option C-1: NJ-600, 600mm 2-layer 3-travel universal rail (cabinet internal depth 600~1200mm compliant)

Option C-2: 1234U-RMK, 1234U rear mounting kit

Option D-0: C335B-35BK, Twin 3.5" FDD bay (two 3.5" FDD devices can be installed in this Twin 3.5" FDD bay)

Option D-1: RW225-M2, 1x3.5" FDD to 2 x M.2 SSD Removable Cage M.2 NVMe 64G

Option D-2: RW125-NVMe, 1x3.5" FDD to 1x2.5" SSD Removable Cage U.2 NVMe 32G

Option D-3: RW125-12G, 1x3.5" FDD to 1x2.5" HotSwap Cage SATA/SAS 12G

Option D-4: TL125-12G, 1x3.5" FDD to 1x2.5" TrayLess HotSwap Cage SATA/SAS 12G

Option D-5: TL225, 1x3.5" FDD to 2x2.5" TrayLess HotSwap Cage SATA/SAS 12G

Option E-1: RW135-12G, 1x5.25" to 1x3.5" HotSwap Cage SATA/SAS 12G

Option E-2: TL135-12G, 1x5.25" to 1x3.5" TrayLess HotSwap Cage SATA/SAS 12G

Option E-3: RW225-NVMe-U, 1x5.25" to 2xUSB3 2x2.5" SSD Removable Cage U.2 NVMe 32G

Option E-4: RW225-NVMe, 1x5.25" to 2x2.5" SSD Removable Cage U.2 NVMe 32G

Option E-5: RW225-12G, 1x5.25" to 2x2.5" HotSwap Cage SATA/SAS 12G

Option E-6: RW625-12G, 1x5.25" to 6x2.5" HotSwap Cage SATA/SAS 12G

Option E-7: RW825-1525, 1x5.25" to 8x2.5" HotSwap Cage SATA/SAS 6G

Option E-8: RW425-NVMe, 1x5.25" to 4x2.5" SSD Removable Cage U.2 NVMe 32G

Option E-9: RW425-12G-MS, 1x5.25" to 4x2.5" HotSwap Cage SFF-8643 12G

Option E-10: RW425-12G, 1x5.25" to 4x2.5" HotSwap Cage SATA/SAS 12G

Option E-11: RW425, 1x5.25" to 4x2.5" HotSwap Cage SATA/SAS 6G

Option F-1: 1MSAS-4SATA-500MM, SFF-8087 Mini-SAS (Host) to Four SATA (Device) cable

Option F-2: SFF-8643-500MM, SFF-8643 Mini-SAS HD (Host) to SFF-8643 Mini-SAS HD (Device) cable

Option F-3: 4SATA-SFF-8643-500MM, Four SATA (Host) to SFF-8643 Mini-SAS HD (Device) cable

Option F-4: SFF-8643-4SATA-500MM, SFF-8643 Mini-SAS HD (Host) to Four SATA (Device) cable

Option G-1: 2U2011A-8080, 2U Intel LGA2011 LGA2066 active CPU cooler Square (2U 3U 4U chassis compatible)

Option G-2: 2U2011A-5694, 2U Intel LGA2011 active CPU cooler Narrow (2U 3U 4U chassis compatible)

Option G-3: 2U115XA, 2U Intel LGA115x Xeon 1230 active CPU cooler (2U 3U 4U chassis compatible)

Option G-4: 2U4094A-SP3, 2U AMD EPYC LGA4094 active CPU cooler SP3 (2U 3U 4U chassis compatible)


Option G-5: 2U1331A-AM4, 2U AMD LGA1331 active CPU cooler AM4 (2U 3U 4U chassis compatible)

Option G-6: 2U3647A-S82, 2U Intel LGA3647 active CPU cooler Square (2U 3U 4U chassis compatible)


Option G-7: 2U3647A-R82-1, 2U Intel LGA3647 active CPU cooler Narrow (2U 3U 4U chassis compatible)

Option G-8: 2U4189A-M82, 2U Intel LGA4189 active CPU cooler (2U 3U 4U chassis compatible)

Option G-9: 2U1700A-V15, 2U Intel LGA1700 active CPU cooler (2U 3U 4U chassis compatible)



The room between top (lid) of this 3U chassis and expansion card bracket is maximum 11.00mm



7 slots and I/O front access



5.25" ODD front access

Latest updated on June 13, 2023

当社の書面許可しない場合に勝手に製品の設計、写真、規格説明など使っては禁止されております。法律顧問: Guan-Rong Attorney-AT-LAW

GeneSys Group Corporation copyright reserved © Without official document authorized by our company, any commercial behaviors including product design, photograph and specification description are prohibited. Website: www.genesysgroup.com.tw