

2U black MicroATX enterprise server chassis

The most obvious feature of this E239B chassis is its depth 385mm only. In addition, its unique stylish mechanism and excellent ventilation as well as the dust-proof design are also the major characteristics. The main structure made by 1.2mm SGCC ultra high strength sheet metal plate with no sharp corners and burrs. The front security door design also ensure data security and avoid improper burning discs or USB drive to copy data security vulnerabilities caused. This model can be installed in addition to the regular standard MicroATX 9.6" x9.6" motherboard, also compatible with the smaller size of server motherboard such as Mini-ITX form factor, for a variety of system environments, the good price competition and the advantage of this chassis design, welcome worldwide distribution.



Specification

- * Totally 6 drive bays: 2 x 5.25" ODD, 2 x 3.5" HDD, 2 x 2.5" HDD (max. height at 9.5mm)
- * Drive bay equipped with anti-vibration function, extend storage appliance life
- * Removable front keylock security door with dustproof filter
- * Two USB 3.0 ports behind the front keylock security door (USB 2.0 also compatible)
- * Main structure of SGCC sheet metal thickness at 1.2mm with protective sheet on surface
- * Two 60mmx25mm intake 2ball fans with dustproof filter at front (fan part# DF6025HB1)
- * Room noise without fan activated is 45dBA, tested by 10cm distance to the running fan is 55dBA (including room noise)
- * Compatible motherboard: MicroATX(9.6"x9.6"), Mini-ITX(6.7"x6.7")
- * Support PS2 8cm or 12cm~14cm fan version psu (max. psu depth at 140mm~180mm)
- * If 140mm deep PS2 psu installed, 5.25" ODD device by 220mm deep also compatible
- * If 180mm deep PS2 psu installed, 5.25" ODD device by 170mm deep also compatible
- * If front fixed with 3.5" HDD, 4 slot low profile plugin cards (max. depth 170mm)
- * If front fixed w/o 3.5" HDD & bracket, 4 slot low profile plugin cards (max. depth 330mm)
- * Standard paint: black at front
- * Genesys Group branded server chassis model (with build-in fans) global 3 years warranty
- * Chassis dimension: 19" x 2U x 385mm (15.16" deep)
- * Accessory pack: M3 truss head screw x 8cs, #6 round head screw x 20pcs, metal stand-off x 10pcs, key x 2pcs
- * Package: NW 6.5 KGM, GW 8 KGM, 1.63 CUFT (54.5x54.5x15.5cm, durable carton packed)



Ordering Information

- Model#: E239B, 2U black MicroATX enterprise server chassis
- Option A: PS2 8cm or 12cm~14cm fan version power supply (max. psu depth at 140mm~180mm)
 - Option B-1: NJ-600, 600mm 2-layer 3-travel universal slide rail (part# is 1 pair, cabinet internal depth 600~1200mm compliant)
 - Option B-2: 1234U-RMK, 1234U rear mounting kit (part# is 1 pair)
 - Option C: 25-35-BK, 5.25" 3.5" 2.5" multiple HDD bracket
 - Option D-1: 2525TO3HDBK, 2x5.25" ODD space to 3x3.5" bracket
 - Option D-2: RW425-12G, 1x5.25" to 4x2.5" SAS12G Hot-Swap Cage
 - Option D-3: RW825-12G, 2x5.25" to 8x2.5" SAS12G Hot-Swap Cage
 - Option D-4: RW425, 1x5.25" to 4x2.5" SAS/SATA Hot-Swap Cage
 - Option D-5: RW825, 2x5.25" to 8x2.5" SAS/SATA Hot-Swap Cage
 - Option D-6: RW335, 2x5.25" to 3x3.5" SAS/SATA Hot-Swap Cage
 - Option D-7: TL335, 2x5.25" to 3x3.5" TrayLess SAS/SATA Hot-Swap Cage
 - Option D-8: TL135, 1x5.25" to 1x3.5" TrayLess SAS/SATA Hot-Swap Cage
 - Option D-9: RW135, 1x5.25" to 1x3.5" SAS/SATA Hot-Swap Cage
 - Option E-1: 1MSAS-4SATA-500MM, SFF-8087 Mini-SAS (Host) to Four SATA (Device) cable
 - Option E-2: SFF-8643-500MM, SFF-8643 Mini-SAS HD (Host) to SFF-8643 Mini-SAS HD (Device) cable
 - Option F-1: 2U2011A-8080, 2U Intel LGA2011 active CPU cooler Square (2U 3U 4U chassis compatible)
 - Option F-2: 2U2011A-5694, 2U Intel LGA2011 active CPU cooler Narrow (2U 3U 4U chassis compatible)



Latest updated on June 28, 2016