

In line with the installation of MicroATX motherboard, but also in line with the server and storage system or cloud requirement nowadays, the depth of this chassis is only 430mm, the robust mechanism strength, the optional hotswap HDD mobile rack can be installed at front side of chassis, and optional hotswap redundant power supply can be installed at rear side of chassis, two sides of chassis can be also installed with durable strength slide rails as option, convenient and rapid implementation of system maintenance and maintenance. This server combines the advantages of multi-functional, price also absolutely has the advantage of competition, welcome world distribution.

Specification

- * Storage capacity: 2 x 5.25" ODD, 2 x 3.5" HDD
- * HDD bay equipped with damping function reduces vibration & improve storage life
- * Equipped with high strength aluminum die-casting handles as standard
- * Front bezel equipped with two USB 3.0 ports and LAN/HDD/Power LED
- * Removable front door with security keylock and air filter function
- * Two brand new low noise 80mmx25mm intake fans at front (part# D80SM-12)
- * Compatible motherboard: MicroATX(9.6"x9.6"), Mini-ITX(6.7"x6.7")
- * Support 4-slot low profile height expansion cards at maximum 255mm deep
- * Front-Right without 5.25" installed, max. 250mm deep PSU supported
- * Front-Right with 210mm deep 5.25" installed, max. 200mm deep PSU supported
- * 8cm or 12cm~14cm fan version standard PS2 power supply compatible
- * Support SureStar R4S series 400W~500W PS2 Mini Redundant PS (depth 174mm)
- * Support Zippy MRT & MRW series 300W~600W PS2 Mini Redundant PS (depth 185mm)
- * Support SureStar R4B series 600W~800W PS2 Mini Redundant PS (depth 199mm)
- * Support Zippy MRG series 500W~800W PS2 Mini Redundant PS (depth 200mm)
- * Sheet metal by SECC 1.2mm~2.0mm thickness with no burr & sharp corner design
- * Standard paint: scratch-resistant black textured at front
- * Genesys Group branded server chassis in global 3 years warranty
- * Chassis dimension: 19" x 2U x 430mm (16.93" deep)
- * Accessory: #6 round x20, M3 truss x8, #6 countersunk x2, key x2
- * Package: NW 5.50 KGM, GW 7.20 KGM, 1.88 CUFT (carton size at 56x56x17cm)

Ordering Information

- Model#: E243B-mATX 2U black MicroATX enterprise server chassis
- Option A-1: 8cm & 12cm & 14cm fan version PS2 power supply
 - Option A-2: SureStar R4S series 400W/500W PS2 Mini Redundant PS (depth at 174mm)
 - Option A-3: Zippy MRT & MRW series 300W~600W PS2 Mini Redundant power supply (depth at 185mm)
 - Option A-4: SureStar R4B series 600W/700W/800W PS2 Mini Redundant PS (depth at 199mm)
 - Option A-5: Zippy MRG series 500W~800W PS2 Mini Redundant power supply (depth at 200mm)
 - Option B-1: NJ-600 600mm 2-layer 3-travel universal rail (cabinet internal depth 600mm~1200mm compliant)
 - Option B-2: NJ-2020-18 18-inch full extension slide rail (cabinet internal depth 456.7mm~810mm compliant)
 - Option B-3: 1234U-RMK 1234U rear mounting kit
 - Option C: 25-35-BK 5.25" 3.5" 2.5" multiple HDD bracket
 - Option D-1: 2525T03HDBK 2x5.25" to 3x3.5" bracket
 - Option D-2: RW135-12G 1x5.25" to 1x3.5" HotSwap Cage SATA/SAS 12G
 - Option D-3: RW135 1x5.25" to 1x3.5" HotSwap Cage SATA/SAS 6G
 - Option D-4: TL135-12G 1x5.25" to 1x3.5" TrayLess HotSwap Cage SATA/SAS 12G
 - Option D-5: TL135 1x5.25" to 1x3.5" TrayLess HotSwap Cage SATA/SAS 6G
 - Option D-6: RW225-12G 1x5.25" to 2x2.5" HotSwap Cage SATA/SAS 12G
 - Option D-7: RW625-12G 1x5.25" to 6x2.5" HotSwap Cage SATA/SAS 12G
 - Option D-8: RW825-1525 1x5.25" to 8x2.5" HotSwap Cage SATA/SAS 6G
 - Option D-9: RW425-12G-MS 1x5.25" to 4x2.5" HotSwap Cage SFF-8643 12G
 - Option D-10: RW425-12G 1x5.25" to 4x2.5" HotSwap Cage SATA/SAS 12G
 - Option D-11: RW425 1x5.25" to 4x2.5" HotSwap Cage SATA/SAS 6G
 - Option D-12: RW825 2x5.25" to 8x2.5" HotSwap Cage SATA/SAS 6G
 - Option D-13: RW335-12G 2x5.25" to 3x3.5" HotSwap Cage SATA/SAS 12G
 - Option D-14: RW335 2x5.25" to 3x3.5" HotSwap Cage SATA/SAS 6G
 - Option D-15: TL335-12G 2x5.25" to 3x3.5" TrayLess HotSwap Cage SATA/SAS 12G
 - Option D-16: TL335 2x5.25" to 3x3.5" TrayLess HotSwap Cage SATA/SAS 6G
 - Option E-1: 1MSAS-4SATA-500MM SFF-8087 Mini-SAS (Host) to Four SATA (Device) cable
 - Option E-2: SFF-8643-500MM SFF-8643 Mini-SAS HD (Host) to SFF-8643 Mini-SAS HD (Device) cable
 - Option E-3: 4SATA-SFF-8643-500MM Four SATA (Host) to SFF-8643 Mini-SAS HD (Device) cable
 - Option E-4: SFF-8643-4SATA-500MM SFF-8643 Mini-SAS HD (Host) to Four SATA (Device) cable
 - Option F-1: 2U2011A-8080 2U Intel LGA2011 LGA2066 active CPU cooler Square (2U 3U 4U chassis compatible)
 - Option F-2: 2U2011A-5694 2U Intel LGA2011 active CPU cooler Narrow (2U 3U 4U chassis compatible)
 - Option F-3: 2U1150A 2U Intel LGA115x Xeon 1230 active CPU cooler (2U 3U 4U chassis compatible)
 - Option F-4: 2U4094A 2U AMD EPYC SP3 LGA4094 active CPU cooler (2U 3U 4U chassis compatible)
 - Option F-5: 2U3647A-S82 2U Intel LGA3647 active CPU cooler Square (2U 3U 4U chassis compatible)
 - Option F-6: 2U3647A-R82-1 2U Intel LGA3647 active CPU cooler Narrow (2U 3U 4U chassis compatible)

