



Specification

- * 磁碟機空間: 2組5.25吋ODD, 2組3.5吋HDD, 2組2.5吋SSD (高度7mm~9.5mm硬碟皆相容)
- * 標準內建新巨MRW-5500V4V前置式500W redundant power supply with PFC
- * 採用高強度之鋁合金壓鑄把手
- * 板金主架構採用1.2mm~2.0mm SGCC無花鋼板, 切斷面皆採平滑折邊設計
- * 前面板配備2組高傳輸速度USB 3.0傳輸埠
- * 標準配備4顆全新穩定低噪音80mmx25mm內吸式靜音風扇 (風扇料號D80SM-12)
- * 標準配備風扇接頭集成PCB電路背板 (中間風牆部分)
- * 支援主機板: ATX(12吋x9.6吋), MicroATX(9.6吋x9.6吋), Mini-ITX(6.7吋x6.7吋)
- * 支援3 slot全高式介面卡, 須選購搭配2U轉接卡 (全高式介面卡可支援最大長度290mm)
- * 可選購各式2u riser card, 須事先告知主機板型號以便搭配適合轉接卡與支架以及3槽機箱後板
- * 後板提供1組新巨熱插拔電源TTL訊號傳輸埠 (插座及線材為選配)
- * 標準烤漆顏色: 高強度耐刮傷黑色纖維烤漆於機構前部
- * 台灣工控全球品質保固三年(含所有電子零組件)
- * 機型外型尺寸: 19" x 2U x 600mm (23.62吋深)
- * 零件包明細: Chassis螺絲x52, 主機板墊高柱x10, 電源專用M3長螺絲x2
- * 包裝明細: NW 11.17KG, GW 13.50KG, 3.59 CUFT (carton size at 73x58x24cm)

Ordering Information

機種型號: C260B, 2U mATX ATX RPS rackmount chassis

選配A: 2U riser card (請告知主機板型號及擴充卡型號以便推薦相容的轉接卡)

選配B-1: NJ-S628, 628mm 3-travel slimline slide rail (此料號每單位為1雙, 可相容機櫃外部深度700mm~1000mm)

選配B-2: SRMK-550, 550mm Slimline rear mounting kit 後端支架(此料號每單位為1雙)

選配C-1: 25-35-BK, 1組5.25吋空間轉1顆3.5吋支架, 或者亦可1組3.5吋空間轉2顆2.5吋支架

選配C-2: RW135-12G, 1組5.25吋空間轉1顆3.5吋熱插拔抽取盒SATA/SAS 12G

選配C-3: RW135, 1組5.25吋空間轉1顆3.5吋熱插拔抽取盒SATA/SAS 6G

選配C-4: TL135-12G, 1組5.25吋空間轉1顆3.5吋TrayLess熱插拔抽取盒SATA/SAS 12G

選配C-5: TL135, 1組5.25吋空間轉1顆3.5吋TrayLess熱插拔抽取盒SATA/SAS 6G

選配C-6: RW225-12G, 1組5.25吋空間轉2顆2.5吋熱插拔抽取盒SATA/SAS 12G

選配C-7: RW625-12G, 1組5.25吋空間轉6顆2.5吋熱插拔抽取盒SATA/SAS 12G

選配C-8: RW825-1525, 1組5.25吋空間轉8顆2.5吋熱插拔抽取盒SATA/SAS 6G

選配C-9: RW425-NVMe, 1組5.25吋空間轉4顆2.5吋插拔抽取盒U.2 NVMe 32G

選配C-10: RW425-12G-MS, 1組5.25吋空間轉4顆2.5吋熱插拔抽取盒SFF-8643 12G

選配C-11: RW425-12G, 1組5.25吋空間轉4顆2.5吋熱插拔抽取盒SATA/SAS 12G

選配C-12: RW425, 1組5.25吋空間轉4顆2.5吋熱插拔抽取盒SATA/SAS 6G

選配D-1: 2525TO3HDBK, 2組5.25吋空間轉3顆3.5吋支架

選配D-2: RW825, 2組5.25吋空間轉8顆2.5吋熱插拔抽取盒SATA/SAS 6G

選配D-3: RW335-12G, 2組5.25吋空間轉3顆3.5吋熱插拔抽取盒SATA/SAS 12G

選配D-4: RW335, 2組5.25吋空間轉3顆3.5吋熱插拔抽取盒SATA/SAS 6G

選配D-5: TL335-12G, 2組5.25吋空間轉3顆3.5吋TrayLess熱插拔抽取盒SATA/SAS 12G

選配D-6: TL335, 2組5.25吋空間轉3顆3.5吋TrayLess熱插拔抽取盒SATA/SAS 6G

選配E-1: 1MSAS-4SATA-500MM, SFF-8087 Mini-SAS (Host) to Four SATA (Device) cable

選配E-2: SFF-8643-500MM, SFF-8643 Mini-SAS HD (Host) to SFF-8643 Mini-SAS HD (Device) cable

選配E-3: 4SATA-SFF-8643-500MM, Four SATA (Host) to SFF-8643 Mini-SAS HD (Device) cable

選配E-4: SFF-8643-4SATA-500MM, SFF-8643 Mini-SAS HD (Host) to Four SATA (Device) cable

選配F-1: 2U2011A-8080, 2U Intel LGA2011 LGA2066 active CPU cooler Square (2U 3U 4U chassis compatible)

選配F-2: 2U2011A-5694, 2U Intel LGA2011 active CPU cooler Narrow (2U 3U 4U chassis compatible)

選配F-3: 2U1150A, 2U Intel LGA115x Xeon 1230 active CPU cooler (2U 3U 4U chassis compatible)

選配F-4: 2U4094A-SP3, 2U AMD EPYC LGA4094 active CPU cooler SP3 (2U 3U 4U chassis compatible)

選配F-5: 2U1331A-AM4, 2U AMD LGA1331 active CPU cooler AM4 (2U 3U 4U chassis compatible)

選配F-6: 2U3647A-S82, 2U Intel LGA3647 active CPU cooler Square (2U 3U 4U chassis compatible)

選配F-7: 2U3647A-R82-1, 2U Intel LGA3647 active CPU cooler Narrow (2U 3U 4U chassis compatible)

