



Specification

- * Drive bay: 2 x 5.25" ODD, 2 x 3.5" HDD, 2 x 2.5" HDD (max. SSD height at 9.5mm)
- * Build-in Zippy MRW-5500V4V front-access 500W redundant power supply with PFC
- * High strength aluminum alloy die casting handles ensure stability during rackmounting
- * SGCC sheet metal works at 1.2mm~2.0mm thickness mechanical construction
- * Two USB 3.0 ports and LAN/HDD/Power LED at front bezel
- * Standard with four brand new 80mmx25mm intake fans (fan part# D80SM-12)
- * Standard with multi fan connector PCB in the middle fan wall
- * Compatible MB: ATX(12"x9.6"), MicroATX(9.6"x9.6"), Mini-ITX(6.7"x6.7")
- * 3-slot full high plugin cards compatible if via optional riser card (max. 290mm deep)
- * Various 2U riser cards as option, please inform MB model# to fit proper riser card
- * One TTL signal connector linked with Zippy redundant power supply (option)
- * Standard paint: scratch-resistant black textured paint at front
- * Genesys Group chassis with build-in electronics in global 3 years warranty
- * Chassis dimension: 19" x 2U x 600mm (23.62" deep)
- * Accessory: Chassis screw x52, MB stand-off x10, PSU M3 long screw x2
- * Package: NW 11.17KG, GW 13.50KG, 3.59 CUFT (carton size at 73x58x24cm)

Ordering Information

Model#: C260B, 2U mATX ATX RPS rackmount chassis

- Option A: 2U riser card (To fit proper riser card, please inform MB & plugin card model# in advance)
- Option B-1: NJ-S628, 628mm 3-travel slimline slide rail (compatible cabinet external depth 700~1000mm)
- Option B-2: SRMK-550, 550mm Slimline rear mounting kit
- Option C-1: 25-35-BK, 1x5.25" to 1x3.5" HDD or 1x3.5" to two 2.5" SSD bracket
- Option C-2: RW135-12G, 1x5.25" to 1x3.5" HotSwap Cage SATA/SAS 12G
- Option C-3: RW135, 1x5.25" to 1x3.5" HotSwap Cage SATA/SAS 6G
- Option C-4: TL135-12G, 1x5.25" to 1x3.5" TrayLess HotSwap Cage SATA/SAS 12G
- Option C-5: TL135, 1x5.25" to 1x3.5" TrayLess HotSwap Cage SATA/SAS 6G
- Option C-6: RW225-12G, 1x5.25" to 2x2.5" HotSwap Cage SATA/SAS 12G
- Option C-7: RW625-12G, 1x5.25" to 6x2.5" HotSwap Cage SATA/SAS 12G
- Option C-8: RW825-1525, 1x5.25" to 8x2.5" HotSwap Cage SATA/SAS 6G
- Option C-9: RW425-NVMe, 1x5.25" to 4x2.5" SSD Removable Cage U.2 NVMe 32G
- Option C-10: RW425-12G-MS, 1x5.25" to 4x2.5" HotSwap Cage SFF-8643 12G
- Option C-11: RW425-12G, 1x5.25" to 4x2.5" HotSwap Cage SATA/SAS 12G
- Option C-12: RW425, 1x5.25" to 4x2.5" HotSwap Cage SATA/SAS 6G
- Option D-1: 2525TO3HDBK, 2x5.25" to 3x3.5" bracket
- Option D-2: RW825, 2x5.25" to 8x2.5" HotSwap Cage SATA/SAS 6G
- Option D-3: RW335-12G, 2x5.25" to 3x3.5" HotSwap Cage SATA/SAS 12G
- Option D-4: RW335, 2x5.25" to 3x3.5" HotSwap Cage SATA/SAS 6G
- Option D-5: TL335-12G, 2x5.25" to 3x3.5" TrayLess HotSwap Cage SATA/SAS 12G
- Option D-6: TL335, 2x5.25" to 3x3.5" TrayLess HotSwap Cage SATA/SAS 6G
- Option E-1: 1MSAS-4SATA-500MM, SFF-8087 Mini-SAS (Host) to Four SATA (Device) cable
- Option E-2: SFF-8643-500MM, SFF-8643 Mini-SAS HD (Host) to SFF-8643 Mini-SAS HD (Device) cable
- Option E-3: 4SATA-SFF-8643-500MM, Four SATA (Host) to SFF-8643 Mini-SAS HD (Device) cable
- Option E-4: SFF-8643-4SATA-500MM, SFF-8643 Mini-SAS HD (Host) to Four SATA (Device) cable
- Option F-1: 2U2011A-8080, 2U Intel LGA2011 LGA2066 active CPU cooler Square
- Option F-2: 2U2011A-5694, 2U Intel LGA2011 active CPU cooler Narrow
- Option F-3: 2U1150A, 2U Intel LGA115x Xeon 1230 active CPU cooler
- Option F-4: 2U4094A-SP3, 2U AMD EPYC LGA4094 active CPU cooler SP3
- Option F-5: 2U1331A-AM4, 2U AMD LGA1331 active CPU cooler AM4
- Option F-6: 2U3647A-S82, 2U Intel LGA3647 active CPU cooler Square
- Option F-7: 2U3647A-R82-1, 2U Intel LGA3647 active CPU cooler Narrow

