C338B
3U black ATX ultra cool server chassis

3U C338B架構主要採用1.2mm~2.0mm高強度鋼板, 機構堅固耐用並兼具安全保護特性. 此產品全程採用高級電子材料並具備國際正式安規認證, 同時提供全球品質保證三年之服務. C338B機型最大特色之一就是機身深度只有380mm, 搭配最低廉的成本與最高的品質, 標準配備2組雙滾珠8cm內吸式風扇於防塵前板內. 此外亦可選配2組雙滾珠外吹式6cm風扇於後窗, 符合7~9組存儲空間設計以及標準ATX 12"x9.6"或者MicroATX 9.6"x9.6"主機板. 在一般伺服器或者中小企業型主機的使用環境上, 皆結合了多功能的優點, 價格上也絕對具有競爭之優勢, 歡迎全世界客戶經銷.

Specification

* 共計7~9組存儲空間容量說明如下:
  2組5.25吋ODD, 5組3.5吋HDD bay (如主機板為12"x9.6" ATX)
  或者3組5.25吋ODD, 5組3.5吋HDD bay (如主機板為9.6"x9.6" MicroATX)
  或者2組5.25吋ODD, 6組3.5吋HDD bay (如主機板為9.6"x9.6" MicroATX)
  或者2組5.25吋ODD, 5組3.5吋, 2組2.5吋HDD bay (如主機板為9.6"x9.6" MicroATX)
* HDD磁碟架配備減震功能, 有效提高硬碟壽命
* 主架構採用1.2mm~2.0mm高強度SGCC無花鋼板
* 標準配備2組USB 2.0以及LAN/HDD/Power LED燈號顯示 (選購: 亦可改裝成2組USB 3.0版本)
* 2顆80mmx25mm內吸式雙滾珠風扇附防塵濾網前板 (風扇料號SunTai8025)
* 支援主機板: ATX(12吋x9.6吋), MicroATX(9.6吋x9.6吋), Mini-ITX(6.7吋x6.7吋)
* 支援標準8cm與12cm~14cm風扇版本之PS2 PSU (可支援power最大深度140mm~180mm)
* 如安裝PS2 power supply為標準140mm深度時則可相容於210mm深度之5.25" ODD裝置
* 如安裝PS2 power supply為180mm深度時則可相容於170mm深度之5.25" ODD裝置
* 如前面安裝3.5吋HDD時則支援4 slot 全高介面卡(最大長度170mm)
* 如前面無安裝3.5吋HDD及其支架時則支援4 slot 全高介面卡(最大長度330mm)
* 標準烤漆顏色: 高強度耐刮傷黑色織紋烤漆或者高強度耐刮傷RAL 9018電腦白色織紋烤漆
* 台灣工控全球品質保固三年(含所有電子零組件)
* 機型外型尺寸: 19" x 3U x 380mm (14.96"深)
* 零件包明細: 各式螺絲x32pcs, MB金屬螺柱x2pcs, MB塑膠間隔柱x1pcs
* 包裝明細: NW 6 KGM, GW 8 KGM, 2.31 CUFT (紙箱尺寸57x51x22.5cm)
* 注意: 全高顯示卡的上方若有電源接頭, 所有3U機箱皆不適用, 建議使用4U機箱

Ordering Information

機種型號: C338B, 3U black ATX ultra cool server chassis
選配A: 支援標準8cm與12cm~14cm風扇版本之PS2 power supply (可支援電源深度140mm~180mm)
選配B: SunTai6025, 尚太60mm x 25mm外吹式風扇(此料號每單位為1個, 可安裝2個於後窗上方)
選配C-1: NJ-600, 65公斤超耐重萬用三節式滑軌, 可兼容機櫃內深度600mm~1200mm (料號每單位為1雙)
選配C-2: 1234U-RMK, 1234U共用後端支架 (此料號每單位為1雙)
選配D-1: 25-35-BK, 1組5.25吋空間轉1顆3.5吋支架, 或者亦可1組3.5吋空間轉2顆2.5吋支架
選配D-2: RW4M2, 1組5.25吋空間轉4條M.2 SSD插拔抽取盒M.2 NVMe 64Gbps
選配D-3: RW8M2, 1組5.25吋空間轉8條M.2 SSD插拔抽取盒M.2 NVMe 64Gbps
選配D-4: RW135-12G, 1組5.25吋空間轉1顆3.5吋熱插拔抽取盒SATA/SAS 12G
選配D-5: TL135-12G, 1組5.25吋空間轉1顆3.5吋TrayLess熱插拔抽取盒SATA/SAS 12G
選配D-6: RW225-NVMe-U, 1組5.25吋空間轉2組USB 3.0及2顆2.5吋插拔抽取盒U.2 NVMe 32G
選配D-7: RW225-NVMe, 1組5.25吋空間轉2顆2.5吋插拔抽取盒U.2 NVMe 32G
選配D-8: RW225-12G, 1組5.25吋空間轉2顆2.5吋熱插拔抽取盒SATA/SAS 12G
選配D-9: RW625-12G, 1組5.25吋空間轉6顆2.5吋熱插拔抽取盒SATA/SAS 12G
選配D-10: RW825-1525, 1組5.25吋空間轉8顆2.5吋熱插拔抽取盒SATA/SAS 6G
選配D-11: RW425-NVMe, 1組5.25吋空間轉4顆2.5吋插拔抽取盒U.2 NVMe 32G
選配D-12: RW425-12G-MS, 1組5.25吋空間轉4顆2.5吋熱插拔抽取盒SFF-8643 12G
選配D-13: RW425-12G, 1組5.25吋空間轉4顆2.5吋熱插拔抽取盒SATA/SAS 12G
選配D-14: RW425, 1組5.25吋空間轉4顆2.5吋熱插拔抽取盒SATA/SAS 6G
選配E-1: 2525TO3HDBK, 2組5.25吋空間轉3顆3.5吋支架
選配E-2: RW335-12G, 2組5.25吋空間轉3顆3.5吋熱插拔抽取盒SATA/SAS 12G
選配E-3: TL335-12G, 2組5.25吋空間轉3顆3.5吋TrayLess熱插拔抽取盒SATA/SAS 12G
選配F-1: 3525TO5HDBK, 3組5.25吋空間轉5顆3.5吋支架
選配F-2: RW435-12G-MS, 3組5.25吋空間轉4顆3.5吋熱插拔抽取盒SFF-8643 12G
選配F-3: RW435-12G, 3組5.25吋空間轉4顆3.5吋熱插拔抽取盒SATA/SAS 12G
選配F-4: TL435-12G-MS, 3組5.25吋空間轉4顆3.5吋TrayLess熱插拔抽取盒SFF-8643 12G
選配F-5: TL435-12G, 3組5.25吋空間轉4顆3.5吋TrayLess熱插拔抽取盒SATA/SAS 12G
選配F-6: RW535-12G, 3組5.25吋空間轉5顆3.5吋熱插拔抽取盒SATA/SAS 12G
選配F-7: TL535-12G, 3組5.25吋空間轉5顆3.5吋TrayLess熱插拔抽取盒SATA/SAS 12G
選配G-1: 1MSAS-4SATA-500MM, SFF-8087 Mini-SAS (Host) to Four SATA (Device) cable
選配G-2: SFF-8643-500MM, SFF-8643 Mini-SAS HD (Host) to SFF-8643 Mini-SAS HD (Device) cable
選配G-3: 4SATA-SFF-8643-500MM, Four SATA (Host) to SFF-8643 Mini-SAS HD (Device) cable
選配G-4: SFF-8643-4SATA-500MM, SFF-8643 Mini-SAS HD (Host) to Four SATA (Device) cable
選配H-1: 2U2011A-8080, 2U Intel LGA2011 LGA2066 active CPU cooler Square (2U 3U 4U chassis compatible)
選配H-2: 2U2011A-5694, 2U Intel LGA2011 active CPU cooler Narrow (2U 3U 4U chassis compatible)
選配H-3: 2U115XA, 2U Intel LGA115x Xeon 1230 active CPU cooler (2U 3U 4U chassis compatible)
選配H-4: 2U4094A-SP3, 2U AMD EPYC LGA4094 active CPU cooler SP3 (2U 3U 4U chassis compatible)
選配H-5: 2U1718A-AM5, 2U AMD AM4 AM5 active CPU cooler (2U 3U 4U chassis compatible)
選配H-6: 2U3647A-S82, 2U Intel LGA3647 active CPU cooler Square (2U 3U 4U chassis compatible)
選配H-7: 2U3647A-R82-1, 2U Intel LGA3647 active CPU cooler Narrow (2U 3U 4U chassis compatible)
選配H-8: 2U4189A-M82, 2U Intel LGA4189 active CPU cooler (2U 3U 4U chassis compatible)
選配H-9: 2U1700A-V15, 2U Intel LGA1700 active CPU cooler (2U 3U 4U chassis compatible)



The room between top (lid) of this 3U chassis and expansion card bracket is maximum 8.50mm



最新更新日期: 2024年09月06日

www.genesysgroup.com.tw

当社の書面許可しない場合に勝手に製品の設計、写真、規格説明など使っては禁止されております。 法律顧問: Guan-Rong Attorney-AT-LAW
GeneSys Group Corporation copyright reserved © Without official document authorized by our company, any commercial behaviors including product design, photograph and specification description are prohibited. Website: www.genesysgroup.com.tw