

The brand new 2U multifunctional server chassis has been officially launched today, its rear panel can be compatible to 3 slot riser card or 7 slot low profile card (patented) at the same time, user can select which version to use without changing rear panel at all, the chassis depth has 660mm only but also supports maximum 12"x13" Intel EEB 3.61 eATX serverboard and Intel LGA2011 mounting very well, standard equipped with four high qualified and stable Sunon 2ball bearing 80mm x 25mm fans in the middle fan wall of chassis, the quality perfect and cost effective brand new model, welcome worldwide distribution.



Specification

- * Totally 11 drive bay: 2 x 5.25" DVD and 9 x 3.5" HDD bay
- * drive bay equipped with anti-vibration function
- * with two USB 2.0 ports at front bezel
- * with four Sunon EE80251B1-000C-G99 80mmx25mm intake fans in the middle fan wall
- * Room noise without fan activated is 47dBA, tested by 10cm distance to the running fans is 67dBA (including room noise)
- * with fan connector PCB in the middle fan wall
- * MB: eATX EEB3.61(12"x13"), ATX(12"x9.6"), MicroATX(9.6"x9.6"), Mini-ITX(6.7"x6.7")
- * support PS2 power supply with 80mm fan version (max. psu depth: 160mm)
- * support patented 3 slot full high risers or 7 slot Low Profile cards (max. 342mm long)
- * standard paint: black
- * Genesys Group branded server chassis model (with build-in fans) global 3 years warranty
- * chassis dimension: 19" x 2U x 660mm (25.98" deep)
- * Accessory pack: M3 truss head nickel screw x 8pcs, #6 round head nickel screw x 35pcs, #6 stacked MB stand-off x 5pcs, plastic stand-off x 1pcs, LPF bracket x 6pcs, LPF cover x 1pcs
- * package: NW 9 KGM, GW 12 KGM, 2.66 CUFT (79x56x17cm, single box packed)



Ordering Information

- Model#: E266LB 2U black eATX ultra cool server chassis
- Option A-0: PS2 PSU with PFC and with 80mm fan version (support psu depth 160mm max.)
- Option B-0: NJ-600, 600mm 2-layer 3-travel universal slide rail (part# is 1 pair)
- Option B-1: 1234U-RMK, 1234U rear mounting kit (part# is 1 pair)
- Option C-0: Various 2U riser card
- Option D-0: 25-35-BK, 5.25" 3.5" 2.5" multiple HDD bracket
- Option E-0: 2525TO3HDBK, 2x5.25" ODD space to 3x3.5" bracket
- Option E-1: RW425, 1x5.25" to 4x2.5" SAS/SATA Hot-Swap Cage
- Option E-2: RW825, 2x5.25" to 8x2.5" SAS/SATA Hot-Swap Cage
- Option E-3: RW335, 2x5.25" to 3x3.5" SAS/SATA Hot-Swap Cage
- Option E-4: TL335, 2x5.25" to 3x3.5" TrayLess SAS/SATA Hot-Swap Cage
- Option E-5: TL135, 1x5.25" to 1x3.5" TrayLess SAS/SATA Hot-Swap Cage



Latest updated on March 27, 2015