



Specification

- * 7~9 Drive Capacity:
 2x5.25" ODD, 5x3.5" HDD bay (if 12"x9.6" ATX MB installed)
 or 3x5.25" ODD, 5x3.5" HDD bay (if 9.6"x9.6" MicroATX MB installed)
 or 2x5.25" ODD, 6x3.5" HDD bay (if 9.6"x9.6" MicroATX MB installed)
 or 2x5.25" ODD, 5x3.5" HDD, 2x2.5" HDD bay (if 9.6"x9.6" MicroATX MB installed)
- * Drive bay supported with anti-vibration function that HDD life time extended
- * Main structure of sheet metal by high-class SGCC 1.2mm~2.0mm thickness
- * **Removable** front door with security butterfly keylock and air filter function
- * Equipped two USB 2.0 ports behind the front door
- * Two brand new Sunon EE80251B1-000C-G99 80mmx25mm 2ball fans behind front bezel
- * Room noise without fan activated is 45dBA, tested by 10cm distance to the running fan is 76dBA (including room noise)
- * MB: ATX(12"x9.6")-MicroATX(9.6"x9.6")-Mini-ITX(6.7"x6.7")
- * Support PS2 8cm or 12cm~14cm fan version psu (max. psu depth at 140mm~180mm)
- * If 140mm deep PS2 psu installed, 5.25" ODD device by 210mm deep also compatible
- * If 180mm deep PS2 psu installed, 5.25" ODD device by 170mm deep also compatible
- * If front fixed with 3.5" HDD, 4 slot full high plugin cards (max. depth at 170mm)
- * If front fixed w/o 3.5" HDD & bracket, 4 slot full high plugin cards (max. depth at 330mm)
- * Standard paint: black
- * Genesys Group branded server chassis model (with build-in fans) global 3 years warranty
- * Chassis dimension: 19" x 3U x 380mm (14.96"deep)
- * Accessory pack: M3 truss head screw x 12pcs, #6 round head screw x 36pcs, plastic stand-off x 1pcs, metal stand-off x 2pcs, key x 2pcs
- * Package: NW 7 KGM, GW 9 KGM, 2.22 CUFT (56x51x22cm, single box packed)



Ordering Information

- Model# : E338B 3U black ATX enterprise server chassis
- Option 1-0 : PS2 8cm or 12cm~14cm fan version power supply (max. psu depth at 140mm~180mm)
 - Option 2-0 : SUNON6025, exhaust 60mm x 25mm fan installed above I/O shield of rear panel (part# is 1pcs)
 - Option 3-0 : NJ-600, 600mm 2-layer 3-travel universal slide rail , chassis depth at 600mm~1200mm compatible (part# is 1 pair)
 - Option 3-1 : 1234U-RMK, 1234U rear mounting kit (part# is 1 pair)
 - Option 4-0 : 25-35-BK, 5.25" 3.5" 2.5" multiple HDD bracket
 - Option 5-0 : 2525TO3HDBK, 2x5.25" ODD space to 3x3.5" bracket
 - Option 5-1 : 3525TO5HDBK, 3x5.25" ODD space to 5x3.5" bracket
 - Option 5-2 : RW425, 1x5.25" to 4x2.5" SAS/SATA Hot-Swap Cage
 - Option 5-3 : RW825, 2x5.25" to 8x2.5" SAS/SATA Hot-Swap Cage
 - Option 5-4 : RW1225, 3x5.25" to 12x2.5" SAS/SATA Hot-Swap Cage
 - Option 5-5 : RW335, 2x5.25" to 3x3.5" SAS/SATA Hot-Swap Cage
 - Option 5-6 : RW435, 3x5.25" to 4x3.5" SAS/SATA Hot-Swap Cage
 - Option 5-7 : RW535, 3x5.25" to 5x3.5" SAS/SATA Hot-Swap Cage
 - Option 5-8 : TL335, 2x5.25" to 3x3.5" TrayLess SAS/SATA Hot-Swap Cage
 - Option 5-9 : TL435, 3x5.25" to 4x3.5" TrayLess SAS/SATA Hot-Swap Cage
 - Option 5-10 : TL535, 3x5.25" to 5x3.5" TrayLess SAS/SATA Hot-Swap Cage
 - Option 5-11 : TL135, 1x5.25" to 1x3.5" TrayLess SAS/SATA Hot-Swap Cage



Latest updated on November 14, 2014